

PRIVILEGED AND CONFIDENTIAL INFORMATION

ELIZABETH ANN BEAMON

and

KENNETH F. HUNNICUTT

TITLE OF THE INVENTION

Digital Loop Carrier Module for Proactive Maintenance Application

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Application No. 60/212,207, filed June 16, 2000.

NOTICE OF COPYRIGHT PROTECTION

[0001] A portion of the disclosure of this patent document and its figures contain material subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by anyone of the patent document or the patent disclosure, but otherwise reserves all copyrights whatsoever.

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0002] This invention generally relates to methods for predicting proactive maintenance and, more particularly, to methods and systems for predicting proactive maintenance of the Public Switched Telephone Network.

2. Description of the Related Art

5

10

20

[0006] Individual experience and style also influence proactive maintenance efforts. Some managers strongly believe in proactive maintenance. Other managers are less familiar with proactive maintenance. Telephone customers, as a result, often have differing experiences in quality and service. Some managers know immediately what copper cables and wires are operational and ready for customer use. Other managers have a backlog of repairs and require more time to learn what lines are functioning. This varied management style reduces the ability of telephone companies to execute a unified, customer service plan.

[0007] The manual environment also does not adequately prioritize proactive maintenance. A manager may often have a backlog of proactive maintenance work order. This backlog may be assigned without a focus on the core importance of customer service. A technician, for example, may be assigned to paint a graffiti-covered crossconnect box, even though some customers are without telephone service. The manual environment too easily allows technician efforts to be mistakenly assigned to lower-priority repair work.

[0008] The manual environment also hampers bulk repair efforts. Because the manual environment does not collect and track repair work, managers and technicians have little knowledge of other repair efforts. One technician may be dispatched to a location to repair a single copper cable, and the next day another technician may be dispatched to the same location to repair another copper cable. A single technician, however, could have repaired both copper cables in a single assignment. Bulk repair is especially important when we remember there may be thousands of copper cables branching from the crossconnect boxes. The manual environment hinders managers from assigning and tracking bulk copper cable repairs to avoid unnecessary labor costs.

[0009] The manual environment also inadequately measures technician proficiency. Although some technicians can repair many copper cables in a few hours, other technicians may not be as efficient and may require more time. The manual environment simply counts the number of work orders a technician completed. The manual environment cannot monitor what really matters to internal customers; that is, the actual number of copper cables repaired by the

technician. The manual environment, then, cannot monitor technician efficiency and cannot objectively measure technician performance. The manual environment fails to objectively reward technicians for their actual efforts.

- 5 [0010] There is, accordingly, a need in the art for methods and systems for predicting proactive maintenance of the Public Switched Telephone Network. These methods and systems will preferably monitor and track proactive maintenance procedures, reduce the influence of erratic management styles and beliefs, prioritize and assign bulk proactive maintenance procedures, and objectively measure technician proficiency.

10

BRIEF SUMMARY OF THE INVENTION

00972637 "113000
15 [0011] The aforementioned problems are reduced by a Proactive Maintenance Application. The Proactive Maintenance Application comprises a system that may be implemented in a computer program. The Proactive Maintenance Application acquires information representing many different departments, disciplines, and operations. The Proactive Maintenance Application, for example, may acquire one, or more, of the following types of information: engineering information, customer information, maintenance information, service information, and even real-time process information. The Proactive Maintenance Application acquires
20 information and then combines the information to predict and to prioritize proactive maintenance procedures. Once the Proactive Maintenance Application predicts and prioritizes the proactive maintenance procedures, the Proactive Maintenance Application may even have another feature that creates and dispatches work orders. These work orders describe the proactive maintenance procedures that should be performed. Still another optional feature assigns the work orders to a
25 particular technician. The technician receives the work orders and performs the predicted proactive maintenance procedures.

30 [0012] The Proactive Maintenance Application may be utilized for one or more functions. The Proactive Maintenance Application may monitor proactive maintenance, may assign proactive maintenance, and may track proactive maintenance. Because the Proactive Maintenance

5 Proactive Maintenance Application may also generate work orders describing the predicted proactive maintenance and then track the progress and completion of the work order. The Proactive Maintenance Application may even automatically update the centralized database so that management has a complete, accurate view of equipment and facilities.

10 [0013] The Proactive Maintenance Application may also be utilized to assign proactive
maintenance in bulk. Bulk repairs reduce labor costs and improve revenue. Because the
Proactive Maintenance Application monitors information from many departments, the Proactive
Maintenance Application can assign a single technician to perform many overlapping repairs.
The Proactive Maintenance Application can even identify what specialized skills and equipment
15 will be needed to complete a repair and, once identified, assign those technicians that have the
needed skills and equipment. The Proactive Maintenance Application may thus advantageously
reduce labor costs by reducing redundant technician dispatches. Bulk repairs also quickly
provide more facilities for more customers and, thus, more revenue for the company.

20 **[0014]** It should be understood that the foregoing description of the Proactive Maintenance
Application system is intended to provide an overview of the many separate inventions
encompassed therein. Each of the separate inventive features of the Proactive Maintenance
Application system is described in more detail below.

25 BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

[0015] These and other features, aspects, and advantages of the mobile re-radiating antenna are better understood when the following Detailed Description of the Invention is read with reference to the accompanying drawings, wherein:

FIG. 1 is a block diagram showing the Proactive Maintenance Application residing in a computer system;

FIG. 2 is a block diagram of a communication network representing the operating environment for the Proactive Maintenance Application;

FIG. 3 is a block diagram showing one embodiment of the Proactive Maintenance Application;

FIGS. 4A and 4B are diagrams illustrating a local loop of the Public Switched Telephone Network;

FIG. 5 is a block diagram showing an alternative embodiment of the Proactive Maintenance Application;

FIG. 6 is a block diagram of the Dynamic Network Analyzer Module 104 shown in FIG. 5;

FIG. 7 is a block diagram of the Loop Facilities and Control System Module 106 shown in FIG. 5;

FIG. 8 is a functional block diagram of an alternate embodiment of the Loop Facilities and Control System Module 106 shown in FIG. 5;

FIG. 9 is a functional block diagram of the Technician Dispatch Module 108 shown in FIG. 5;

FIG. 10 is a functional block diagram of an alternate embodiment of the Technician Dispatch Module 108 shown in FIG. 5;

FIG. 11 is a block diagram of the Digital Loop Carrier Module 110 shown in FIG. 5; and

FIG. 12 is a block diagram showing a non-limiting example of the Proactive Maintenance Application.

DETAILED DESCRIPTION OF THE INVENTION

[0016] The present invention particularly relates to methods and systems for proactively maintaining a Digital Loop Carrier in a telephone system local loop. An embodiment of the present invention comprises communicating with a communications network and acquiring status information associated with the Digital Loop Carrier. Proactive maintenance is then predicted

5 may generate and dispatch work order information describing the predicted proactive maintenance.

10 pairs, service information associated with copper line pairs, and status information associated with a Digital Loop Carrier. The acquired information is stored, and the stored information is combined. Proactive maintenance is predicted based upon the combined information. The stored information may be weighted. This embodiment may also generate and dispatch work order information describing the predicted proactive maintenance.

[0018] In another aspect a system of the present invention comprises software modules communicating with a communications network. Some examples of possible software modules include: a Dynamic Network Analyzer module for communicating with the communications network and for acquiring Dynamic Network Analyzer information; a Loop Facilities and Control System module for communicating with the communications network and acquiring Loop Facilities and Control System information, and a Digital Loop Carrier module for communicating with the communications network and for acquiring Digital Loop Carrier information. A database may interface with the modules, with the database storing the acquired information. The system may further comprise a processor capable of processing information stored in the database and of generating proactive maintenance.

[0019] Still another embodiment describes a computer program product for proactively maintaining a telephone system. This computer program product comprises a computer-readable medium and a Digital Loop Carrier module stored on the medium. The Digital Loop Carrier
30 Module couples to a Digital Loop Carrier over a communications network. The Digital Loop

5

15

25

EXPRESS MAIL #EJ841202256US

in a computer system 22. The Proactive Maintenance Application 20 may be stored within a system memory device 24. The computer system 22 also has a central processor 26 executing an operating system 28. The operating system 28 also resides within the system memory device 24. The operating system 28 has a set of instructions that control the internal functions of the computer system 22. A system bus 30 communicates signals, such as data signals, control signals, and address signals, between the central processor 26, the system memory device 24, and at least one peripheral port 32. While the computer system 22 is a Hewlett Packard 9000, those skilled in the art understand that the program, processes, methods, and systems described in this patent are not limited to any particular computer system or computer hardware.

5 [0023] Those skilled in art also understand the central processor 26 is typically a microprocessor. Advanced Micro Devices, Inc., for example, manufactures a full line of ATHLON™ microprocessors (ATHLON™ is a trademark of Advanced Micro Devices, Inc., One AMD Place, P.O. Box 3453, Sunnyvale, California 94088-3453, 408.732.2400, 800.538.8450, www.amd.com). The Intel Corporation also manufactures a family of X86 and P86 microprocessors (Intel Corporation, 2200 Mission College Blvd., Santa Clara, California 95052-8119, 408.765.8080, www.intel.com). Other manufacturers also offer microprocessors. Such other manufacturers include Motorola, Inc. (1303 East Algonquin Road, P.O. Box A3309 Schaumburg, IL 60196, www.Motorola.com), International Business Machines Corp. (New Orchard Road, Armonk, NY 10504, (914) 499-1900, www.ibm.com), and Transmeta Corp. (3940 Freedom Circle, Santa Clara, CA 95054, www.transmeta.com). While only one microprocessor is shown, those skilled in the art also recognize multiple processors may be utilized. Those skilled in the art further understand that the program, processes, methods, and systems described in this patent are not limited to any particular manufacturer's central processor.

[0024] The system memory 24 also contains an application program 34 and a Basic Input/Output System (BIOS) program 36. The application program 34 cooperates with the operating system 28 and with the at least one peripheral port 32 to provide a Graphical User Interface (GUI) 38. The Graphical User Interface 38 is typically a combination of signals communicated along a keyboard port 40, a monitor port 42, a mouse port 44, and one or more drive ports 46. The Basic Input/Output System 36, as is well known in the art, interprets requests from the operating system 28. The Basic Input/Output System 36 then interfaces with the keyboard port 40, the monitor port 42, the mouse port 44, and the drive ports 46 to execute the request.

[0025] The operating system 28 is WINDOWS NT® (WINDOWS NT® is a registered trademark of Microsoft Corporation, One Microsoft Way, Redmond WA 98052-6399, 425.882.8080, www.Microsoft.com). WINDOWS NT® is preinstalled in the system memory device 24 on the Hewlett Packard 500. Those skilled in the art also recognize many other operating systems are suitable, such as UNIX® (UNIX® is a registered trademark of the Open Source Group, www.opensource.org), Linux, and Mac® OS (Mac® is a registered trademark of Apple Computer, Inc., 1 Infinite Loop, Cupertino, CA 95014, 408.996.1010, www.apple.com). Those skilled in the art again understand that the program, processes, methods, and systems described in this patent are not limited to any particular operating system.

[0026] FIG. 2 is a block diagram of a communications network 48. This communications network 48 further represents an operating environment for the Proactive Maintenance Application (shown as reference numeral 20 in FIG. 1). The Proactive Maintenance Application resides within the memory storage device (shown as reference numeral 24 in FIG. 1) in the computer system 22. The computer system 22 is conveniently shown as a computer server 50 representing the Hewlett Packard 500. The computer system 22 communicates with a Local Area Network (LAN) 52 along one or more data communication lines 54. As those skilled in the art have long understood, the Local Area Network 52 is a grid of communication lines through which information is shared between multiple nodes. These multiple nodes are conventionally described as network computers. As those skilled in the art also recognize, the Local Area

5

10

20

maintenance procedures. The Proactive Maintenance Application 20 may further assign weights to each source of information to increase or decrease the influence of either combined component.

- 5 [0029] The engineering information 64 may represent various engineering activities. The engineering information 64, for example, could represent component or system durability test results, model shop equipment errors, or CAD/CAM dimensions and/or tolerances. The engineering information 64 may also represent component or system performance data, material specifications, or even government regulations. Any engineering-type information that could be
10 used to predict proactive maintenance is considered within the ambit of the engineering information 64.

[0030] The customer information 66 may represent various customer activities. The customer information 66, for example, may represent actual customer purchasing preferences, marketing data, or customer product or process improvement suggestions. The customer information 66 may also represent customer demographic data, customer order information, or even customer profiles. Any customer-type information that could be used to predict proactive maintenance is considered within the ambit of the customer information 66.

15 [0031] The maintenance information 68 may represent various maintenance activities. The maintenance information 68, for example, may represent component replacement history, system or process performance history, or equipment repair history. The maintenance information 68 may also represent process measurement data, statistical process control data, maintenance logs, and even technician data. Any maintenance-type information that could be used to predict
20 proactive maintenance is considered within the ambit of the maintenance information 68.

[0032] The service information 70 may represent various service activities. The service information 70, for example, may represent warranty information, unique or special service tooling information, limitations encountered during service repairs, or obstacles encountered
30 during service repairs. The service information 70 may also represent field conditions (e.g.,

temperature, humidity, dust, and dirt), availability of original equipment manufacture (OEM) service parts, or even failure data. Any service-type information that could be used to predict proactive maintenance is considered within the ambit of the service information 70.

5 [0033] The real-time process information 72 may represent various process activities. The real-time process information 72, for example, may represent equipment wear indicators, gauge data, or process data (e.g., mold temperature data, cleaning/washing fluid turbidity data, or machine speed data). The real-time process information 72 may also represent re-work information, shift production data, or even line shut-down indicators. Any process-type
10 information that could be used to predict proactive maintenance is considered within the ambit of the real-time process information 72.

[0034] The Proactive Maintenance Application 20 may even dispatch work orders. Once the Proactive Maintenance Application 20 predicts and prioritizes the proactive maintenance procedures, the Proactive Maintenance Application 20 then interfaces with a technician dispatch system 76 to create and dispatch work orders. These work orders describe the proactive maintenance procedures that should be performed. The Proactive Maintenance Application 20 may even assign the work orders to a particular technician. The technician receives the work orders and performs the predicted proactive maintenance procedures.

20 [0035] Those skilled and even unskilled in the art recognize the Proactive Maintenance Application 20 is applicable to many different environments, industries, and processes. The Proactive Maintenance Application 20 is especially applicable to the Public Switched Telephone Network. The Public Switched Telephone Network (PSTN) is composed of many switches and
25 thousands of copper cables, copper wires, and fiber optic cables. These copper and fiber optic cables are often buried underground, strung from telephone poles, and tucked within the walls of buildings. Because these cables may deteriorate at approximately twelve percent (12%) to fifteen percent (15%) per year, the local telephone carrier needs to proactively maintain the system to provide quality telephone service. If the system is not adequately maintained, customer
30 complaints increase, quality suffers, and costs increase.

5

15

30

100. See THOMPSON, *supra*, at 71. The complexity of the Public Switched Telephone Network is further magnified knowing there are approximately forty thousand (40,000) central offices located throughout the United States. See THOMPSON, *supra*, at 95. Such a complex system, with billions of copper line pairs and fiber optic cables, requires a meticulously detailed, logical, and simple maintenance system to ensure quality telephone service.

10
17
15
20
25

[0039] The Proactive Maintenance Application 20, therefore, is very useful for proactively maintaining the local loops of Public Switched Telephone Network. FIG. 5 is a block diagram showing an alternative embodiment configured for proactively maintaining the local loop (shown as reference numeral 78 in FIG. 4A). The Proactive Maintenance Application Database 74 interfaces with several data sources to predict any needed proactive maintenance. These data interfaces include an Administrative Module 102, a Dynamic Network Analyzer Module 104, a Loop Facilities and Control System Module 106, a Technician Dispatch Module 108, and a Clear Defective Pairs Module 110. A Loop Engineering Information System module may also be included as shown and as described in U.S. Patent Application Serial No. _____, filed concurrently herewith, titled "Proactive Maintenance Application," and incorporated herein by reference in its entirety. The Proactive Maintenance Application Database 74, in addition, accepts manually-entered supervisor data 112 and manually-entered technician data 114. Each interface and data input provides information for predicting proactive maintenance procedures. The Proactive Maintenance Application Database 74 acquires and combines all this information. The Proactive Maintenance Application Database 74 predicts, based upon the combined information, what proactive maintenance procedures should be performed to maintain the local loop. The Proactive Maintenance Application Database 74 prioritizes these proactive maintenance procedures. The Proactive Maintenance Application Database then interfaces with the Technician Dispatch Module 108 to generate and to dispatch proactive maintenance work

orders. These proactive maintenance work orders are assigned to field service technicians, and the field service technicians perform the predicted proactive maintenance procedures.

[0040] The Proactive Maintenance Application 20 may also track the status of work orders.

Not only does the Proactive Maintenance Application 20 prioritize work orders, but the Proactive Maintenance Application 20 also receives progress updates. Users of the Proactive Maintenance Application 20 can learn the date a work order was (or will be) dispatched, the name of any assigned field technician, and whether the field technician has completed the work order. The field technician may even update the Proactive Maintenance Application 20 with progress reports, estimated completion time and date, any needed equipment, or any required support. The Proactive Maintenance Application 20 thus provides a common repository or database of pending and assigned work orders for all users to access and use.

[0041] The Proactive Maintenance Application 20 may also provide historical work order information. Because the Proactive Maintenance Application 20 stores all generated work orders, the Proactive Maintenance Application 20 provides an easy and quick access to historical work order information. The Proactive Maintenance Application 20, for example, could be searched to learn how many times a particular crossconnect has been serviced, how frequently a particular customer's line has been repaired, or what areas are especially prone to repair. This historical information enables the Proactive Maintenance Application 20, and the users of Proactive Maintenance Application 20, to improve proactive maintenance and to thus improve telephone service.

[0042] The Proactive Maintenance Application 20 may be physically embodied on or in a computer-readable medium. This computer-readable medium includes CD-ROM, DVD, tape, cassette, floppy disk, memory card, and a large-capacity disk (such as IOMEGA® ZIP®, JAZZ®, and other large-capacity memory products) (IOMEGA®, ZIP®, and JAZZ® are registered trademarks of Iomega Corporation, 1821 W. Iomega Way, Roy, Utah 84067, 801.332.1000, www.iomega.com). This computer-readable medium, or media, could be distributed to end-users, licensees, and assignees. These types of computer readable media, and



5

10

15

20

Administrative Module 102, in short, manages the Proactive Maintenance Application 20 and pre-populates any administrative data required by other interfaces.

The Dynamic Network Analyzer Module 104

5 [0045] FIG. 6 is a block diagram of the Dynamic Network Analyzer Module 104 shown in FIG. 5. The Dynamic Network Analyzer Module 104 provides historical information to the Proactive Maintenance Application Database 74. The Dynamic Network Analyzer Module 104 communicates with the communications network (shown as reference numeral 48 in FIG. 2) and acquires Dynamic Network Analyzer information 116 from a Dynamic Network Analyzer 118.

10 The Dynamic Network Analyzer 118 is a software application that counts all customer trouble reports since a specific work order was issued or completed. These trouble reports, commonly referred to as Trouble Since Issued (TSI) reports, are utilized to re-prioritize open work orders on a daily basis. Each Trouble Since Issued report is associated with a particular feeder cable (shown as reference numeral 94 in FIGS. 4A and 4B) and a particular copper line pair within that

15 feeder cable. The Dynamic Network Analyzer 118, for example, is typically run every week. The Dynamic Network Analyzer 118 generates a listing of what maintenance needs to be done based upon trouble history from customer trouble reports. The Dynamic Network Analyzer Module 104 communicates with the communications network and acquires the Dynamic Network Analyzer information 116 as an ASCII file. The Proactive Maintenance Application

20 Database 74 acquires this ASCII file to create and prioritize maintenance work orders. The Proactive Maintenance Application Database 74 then interfaces with the Technician Dispatch Module 108 to generate and dispatch proactive maintenance work orders.

The Loop Facilities and Control System Module 106

25 [0046] FIG. 7 is a block diagram of the Loop Facilities and Control System Module 106 shown in FIG. 5. The Loop Facilities and Control System Module 106 communicates with the communications network (shown as reference numeral 48 in FIG. 2) and acquires Pending Service Order Information 120 from a Loop Facilities and Control System 122. The Loop Facilities and Control System 122 maintains an engineering database of pending service orders.

30 The Loop Facilities and Control System 122 provides the status of each copper line pair in a

specified feeder cable (shown as reference numeral 94 in FIGS. 4A and 4B) associated with pending service orders. Pending service orders are conventionally written up manually and distributed from management down to the technician. This conventional distribution process is extremely slow, often requiring several weeks. The Loop Facilities and Control System Module 106, however, acquires the pending service order information 120 and merges the pending service order information 120 into a proactive maintenance work order. The Proactive Maintenance Application Database 74 then interfaces with the Technician Dispatch Module 108 to generate and dispatch proactive maintenance work orders. The field technician can complete both a proactive maintenance work order and a pending service order. The Proactive Maintenance Application 20 thus eliminates the manual paper trail and eliminates the very slow conventional process.

[0047] The Proactive Maintenance Application 20 also permits the technician supervisor to immediately update the Loop Facilities and Control System 122. Once the technician supervisor assigns a particular technician, the technician supervisor can email the pending service order information 120 directly to the field technician. The technician supervisor could alternatively generate the pending service order information 120 to the field technician's computer printer. The field technician receives the pending service order information 120, completes the service order, and returns the completed service order to the technician supervisor. The technician supervisor can then immediately log into the Proactive Maintenance Application 20 and manually update the system with the completed service order. This manually-entered supervisor data 112 is acquired by the Proactive Maintenance Application 20. The Proactive Maintenance Application 20 immediately communicates completed service order information 124 to the Loop Facilities and Control System Module 106. The Loop Facilities and Control System Module 106 communicates this completed service order information 124 to the Loop Facilities and Control System 122. The Loop Facilities and Control System 122 is immediately and automatically updated with any completed service orders.

[0048] The Proactive Maintenance Application 20 is a great improvement. Pending service orders with clear defective pairs were previously manually written and distributed from

management down to the technician. Any pending service order could take weeks to funnel from central management down to the actual field technician. The Proactive Maintenance Application 20, however, compresses the time to complete a pending service order. The Proactive Maintenance Application 20 can now issue a pending service order in minutes. The Proactive Maintenance Application 20 also immediately and automatically updates the Loop Facilities and Control System 122 database of pending service orders. Thus whenever a pending service order is completed, the local telephone service provider knows within minutes that a copper line pair is available for use. The now-available copper line pair is ready to provide telephone service and to generate revenue for the local telephone service provider. The Proactive Maintenance Application 20, therefore, reduces service order response times, improves utilization of copper line pairs, and increases operational revenues.

[0049] FIG. 8 is a functional block diagram of an alternate embodiment of the Loop Facilities and Control System Module 106 shown in FIG. 5. This alternate embodiment allows the field technician to log onto into the Proactive Maintenance Application 20 and manually update the Proactive Maintenance Application 20 with a completed service order. This manually-entered technician data 114 is acquired by the Proactive Maintenance Application Database 74. The Proactive Maintenance Application Database 74 immediately passes the completed service order information 124 to the Loop Facilities and Control System Module 106. The Loop Facilities and Control System Module 106 sends this completed service order information 124 to the Loop Facilities and Control System 122. This embodiment allows the field technician to update the Loop Facilities and Control System 122 without supervisor effort.

The Technician Dispatch Module 108

[0050] FIG. 9 is a functional block diagram of the Technician Dispatch Module 108 shown in FIG. 5. The Technician Dispatch Module 108 not only dispatches proactive maintenance work orders, but the Technician Dispatch Module 108 also tracks field technician proficiencies. Once the Proactive Maintenance Application 20 generates a proactive maintenance work order, the Technician Dispatch Module 108 acquires generated proactive maintenance work order information 126 representing the generated proactive maintenance work order. The Technician

5

10

15

20

system 138 of Digital Loop Carriers. As those skilled in the art of telephony understand, Digital Loop Carriers allow telephone service providers to expand service without adding more copper cables. See THOMPSON, *supra*, at 87. A Digital Loop Carrier multiplexes several telephone customers along a single cable. See *id.* The Digital Loop Carrier Module 110 allows the Proactive Maintenance Application 20 to acquire this Digital Loop Carrier information 136 from a computer monitoring the system 138 of Digital Loop Carriers. The Proactive Maintenance Application 20 uses this Digital Loop Carrier information 136 to predict and to prioritize proactive maintenance work orders. The Proactive Maintenance Application 20 then interfaces with the Technician Dispatch Module 108 to generate and dispatch proactive maintenance work orders.

[0053] The Digital Loop Carrier information 136 may represent several indications of the system 138 of Digital Loop Carriers. The Digital Loop Carrier information 136 may represent various alerts, messages, and other system line records describing the status of the system 138 of Digital Loop Carriers. The Digital Loop Carrier information 136 may represent mechanized loop test data. As those skilled in the art of telephony understand, a mechanized loop test looks for defects in the local loop (shown as reference numeral 36 in FIG. 2A). The mechanized loop test may also be used to test for faults or errors in digital loop carriers within the local loop. The Digital Loop Carrier information 136 may also represent, but is not limited to, Digital Loop Carrier pair gain, a history of information communicated from the Loop Maintenance Operating System 128, trouble ticket information, or frequent Digital Loop Carrier work descriptions. The Digital Loop Carrier information 136 could identify a particular Digital Loop Carrier system requiring service. The Digital Loop Carrier information 136 could signify annual or semi-annual inspections of grounds, cabinets, batteries, alarms, plugs, fans, and other components. Those skilled in the art of computer programming recognize the Digital Loop Carrier information 136 can be any information obtainable from the system 138 of Digital Loop Carriers.

[0054] The Digital Loop Carrier Module 110 may also update the system 138 of Digital Loop Carriers. When the Proactive Maintenance Application 20 generates and dispatches a work order describing proactive maintenance for Digital Loop Carriers, a technician is dispatched and

completes the work order. Either the field supervisor or the field technician manually updates the Proactive Maintenance Application 20 with the completed work order. The Digital Loop Carrier Module 110 then acquires digital loop carrier update information 140 from the Proactive Maintenance Application 20. The Digital Loop Carrier Module 110 communicates this digital loop carrier update information 140 to the system 138 of Digital Loop Carriers. The system 138 of Digital Loop Carriers is then updated with any completed proactive maintenance.

[0055] The Digital Loop Carrier Module 110 also interfaces with the Loop Maintenance Operating System 128. A system user queries the PMA for a field technician to complete a work order on a particular dispatch date. The PMA issues a request 142 for a field technician to the Digital Loop Carrier Module 110. The Digital Loop Carrier Module 110 communicates the request 142 for a field technician to the Loop Maintenance Operating System 128. When a field technician completes a work order corresponding to the request, the Loop Maintenance Operating System 128 communicates notification information 144 to the Digital Loop Carrier Module 110. The Digital Loop Carrier Module 110 in turn communicates the notification information 144 to the PMA. The PMA is notified and the system user has a response to the original query.

EXAMPLE

[0056] The Proactive Maintenance Application 20 is further illustrated by the following non-limiting example. FIG. 12 is a block diagram showing this particular non-limiting example is further configured for proactively maintaining the local loop (shown as reference numeral 78 in FIG. 4A). This non-limiting example is similar to that shown in FIG. 5, however, this example allows the Proactive Maintenance Application Database 74 to be accessed by several user groups. These user groups include a Proactive Analysis and Repair Center 146, a Facilities Analysis and Planning Center 148, a Service Advocate Center 150, a Work Management Center 152, an Address Facilities Inventory Group 154, and Outside Plant Engineers 156. These user groups have authority to access some or all information stored in the Proactive Maintenance Application Database 74. Some user groups may even have authority to alter information stored in the Proactive Maintenance Application Database 74. The Proactive Analysis and Repair Center 146,

for example, has authority to alter the Dynamic Network Analyzer information 116 (shown as reference numeral 116 in FIG. 6). The Facilities Analysis and Planning Center 148, likewise, has authority to assign in bulk any repairs to copper line pairs. The Systems Administrator may authorize as many groups as desired to access and even alter information stored in the Proactive Maintenance Application 20. The Proactive Maintenance Application 20 thus allows dedicated groups to monitor corporate-wide proactive maintenance. This corporate-wide monitoring ensures the local loop is proactively and uniformly maintained in all states and regions.

[0057] Once information is acquired and stored in the Proactive Maintenance Application Database 74, the Proactive Maintenance Application 20 prioritizes proactive maintenance procedures. The Proactive Maintenance Application 20 uses weighted formulas to prioritize proactive maintenance work orders. The weighted formulas predict proactive maintenance for Predictor indications, copper line pair changes, predict proactive maintenance for Dynamic Network Analyzer work orders, and predict proactive maintenance bulk copper line pair recovery. The following paragraphs describe each formula and its associated terms.

[0058] A weighted formula for predicting proactive maintenance using Predictor trends is first described. As those of ordinary skill recognize, Predictor is a computer program that collects nightly switch information. A Predictor module communicates with the communications network and acquires this nightly switch information. The Proactive Maintenance Application uses this nightly switch information to predict proactive maintenance based upon the Predictor trends. The nightly switch information may also be used by the Dynamic Network Analyzer module to predict proactive maintenance and to indicate TSI's since a work order was created and dispatched. The formula

$$\frac{W_1 (FEF0) + W_2 (FEF1) + W_3 (\text{number of defective line pairs}) + W_4 (FEF0SI) + W_5 (FEF1SI)}{\text{Time per task for Predictor packages}}$$

has both weighting variables and terms. The weighting variables are W_1 , W_2 , W_3 , W_4 , and W_5 , while the terms are FEF0, FEF1, FEF0SI, and FEF1SI. The terms "number of defective line pairs" and "Time per task for Predictor packages" are self-evident to those of ordinary skill and

will not be further described. The weighting variables will be later shown and described in a table.

[0059] As those of ordinary skill recognize, the terms are common telephony disposition codes.

5 FEF0, for example, indicates a foreign electromotive force was found on the customer's line. A foreign electromotive force may be discovered during a mechanized loop test. FEF1 indicates a battery is present on the F1 facility or the facilities leaving the central office. FEF0SI indicates a foreign electromotive force since a work order was issued. FEF1SI, likewise, indicates a battery is present since a work order was issued.

10

[0060] A weighted formula for predicting copper line pair changes is next described. The formula is

$$\frac{A + B}{\text{Time per task for a pair change}}$$

15 where

$$A = W_6(\text{Code 4}) + W_7(\text{Code 7}) + W_8(\text{Code 9}) + W_9(\text{Predictor}) \text{ and}$$

$$B = W_{10}(\text{number of defective line pairs}) + W_{11}(\text{TSI4}) + W_{12}(\text{TSI7}) + W_{13}(\text{TSI9}).$$

The formula, as above, has both weighting variables and terms. The weighting variables are W_6 , W_7 , W_8 , W_{11} , W_{12} , and W_{13} , while the terms are Code 4, Code 7, Code 9, TSI4, TSI7, and TSI9. The terms "number of defective line pairs" and "time per task for a pair change" are self-evident to those of ordinary skill and will not be further described. The weighting variables will be later shown and described in a table.

25 [0061] The terms, again, are common telephony disposition codes. Code 4 applies to all troubles found in cables, cable terminals, amplifiers, line wire, load coils and protection, field-located concentrators, field-located carrier equipment, and field-located loop electronics. Code 4 also includes trouble reports resulting from a failure of the outside local loop equipment. Code 7 applies to those trouble reports that are tested and verified without dispatching a field technician.

5 trouble reports referred first to central office forces, but subsequently, dispatched to outside
forces.

reference to FIG. 6) applies to trouble received after the proactive maintenance work orders have been developed, but, not dispatched. TSI4, for example, indicates Code 4 trouble was received after the proactive maintenance work order was predicted. TSI7 and TSI9, similarly, indicate Code 7 trouble or Code 9 trouble, respectively, was received.

15 **[0063]** A weighted formula for predicting Dynamic Network Analyzer proactive maintenance is next described. The formula is

C + D

Time per task for Dynamic Network Analyzer work order

where

$$C = W_{14}(\text{Code 4}) + W_{15}(\text{Code 7}) + W_{16}(\text{Code 9}) + W_{17}(\text{Predictor}) \text{ and}$$

$$D = W_{18}(\text{number of defective line pairs}) + W_{19}(\text{TSI4}) + W_{20}(\text{TSI7}) + W_{21}(\text{TSI9}).$$

25 terms “number of defective line pairs” and “time per task for Dynamic Network Analyzer work
order” are self-evident to those of ordinary skill and will not be further described. The weighting
variables will be later shown and described in a table.

[0064] A weighted formula for predicting bulk copper line pair recovery is next described. The formula is

$$\frac{W_{22}(\text{growth})(\text{number of defective line pairs})}{(\text{number of spare line pairs})(\text{time per task for bulk pair recovery})}$$

The term “growth” is the increase in loop activity created by requests for new service and for new customers. The terms “number of defective line pairs,” “number of spare line pairs,” and “time per task for bulk pair recovery” are again self-evident to those of ordinary skill and will not be further described. The weighting variables are shown and described below.

[0065] The weighting variables are chosen based upon field experience. As those of ordinary skill recognize, the weighting variables are used to adjust predicted results. The predicted results are compared with actual field results. The weighting variables are then adjusted until the predicted results closely approximate actual field results. As those of ordinary skill also recognize, the weighting variables may be continually refined to improve predicted work order results. The table below shows the values of the weighting variables used in the non-limiting example. These weighting variables were selected based upon the actual results of 170 predicted work orders.

<u>Weighting Variable</u>	<u>Value</u>	<u>Weighting Variable</u>	<u>Value</u>
W_1	0.89	W_{12}	0.24
W_2	0.50	W_{13}	0.24
W_3	5.90	W_{14}	0.18
W_4	0.89	W_{15}	0.18
W_5	0.50	W_{16}	0.45
W_6	0.24	W_{17}	13.4
W_7	0.24	W_{18}	0.18
W_8	0.24	W_{19}	0.90
W_9	9.20	W_{20}	0.18
W_{10}	1.60	W_{21}	0.45

W_{11}

0.54

W_{22}

0.08

- [0066] While the present invention has been described with respect to various features, aspects, and embodiments, those skilled and unskilled in the art will recognize the invention is not so
- 5 limited. Other variations, modifications, and alternative embodiments may be made without departing from the spirit and scope of the present invention.

09/26/97 11:30:00